



# DBF

## TRICONE DRILL BIT

# 15 1/2 RS1 UT321

<b>Diameter:</b>	<b>393.7mm (15 1/2")</b>
<b>IADC Code:</b>	<b>115 (125)</b>
<b>Design number:</b>	<b>UT321</b>
<b>State standard designation:</b>	<b>M-ЦГВУ</b>

### Specification

Gradient angle of axle journal	33°
Axle journal offset relative to drill bit axis	10.00 mm
Bearing type	Roller bearing
Sealing	Elastomer
Total number of inserts (inner/heel row)	98 (51/47)
Total number of insert rows (inner/heel row)	9 (6/3)
Number of changeable nozzles	4
Connecting thread	3-177 (7 5/8 REG)
Drill bit net weight, kg	153.00
Drill bit gross weight, kg	157.40

### Purpose

The drill bit is designed for drilling soft formations

### Recommended Drilling Conditions

Rotation speed	200-40 rpm
Thrust load	5.00-22.00 t (11000-48400 lbs)

The lower level of rotation speed value corresponds the upper level of thrust load value and vice versa

### Design Features

Combined circulation (central and side), for which it is necessary to unscrew the screw from the central unit

The leg shirrtail and entering edge are hardfaced with tungsten carbide

The leg is protected with tungsten carbide inserts

Tungsten carbide inserts on cone gage.

